Digital walkie talkies

VHF:136-174MHz / UHF:400-480MHz

450-520MHz / 350-390MHz



- One click alarm
- VOX voice control
- Switching regions
- Scanning function
- Detection
- Working alone
- Encryption function
- Individual, group, and full phone number
- Keyboard/Channel Lock
- Battery reminder
- Direction
- Record for 10 minutes

Product technical parameters

Digital walkie talkies **ET-D330**

Whole product section

Working voltage	7.4V
Battery	2500mAh
Dimensions	125*58*43mm
Weight	285g
Select adjacent channels	⩾ 65dB
Channel spacing	12.5kHz/25KHz
Charging method	Charging base/Type-C fast charging

General parameters

Frequency range	VHF:136-174MHz/UHF:400-480MHz/450-520MHz /350-390MHz
Channel capacity	16
Modulation limitation	±5KHz/±2.5KHz
Simulated sensitivity	0.2μV (12dB SINAD)
Receiver sensitivity	-122dBm(12dB SINAD)

Transmitter port

Output power	10W (Analog)/10W (Digital)
Modulation	25K/16KΦF3E 12.5K/8KΦF3E
Modulation distortion	⩽5%
Frequency stability	±2.5ppm
Adjacent channel power	-67dB
Maximum frequency deviation	25K≦5kHz 12.5K≦2.5kHz

Use environment

Working temperature	-20°C～+60°C

All Accessories


Host


Antenna


Back clip


Battery


Charging base


Sling

Applicable scenarios


Fleet


Tourism


Security


Hotel


Construction site


Warehouse

Guangzhou Etmy Technology Co., Ltd.